

TALAS



The premium truck steel rim



Original equipment manufacturer quality | Powered by Germany |
Available as a complete wheel



www.talas-steel.de

Follow us on



TEP-No.	Wheel size	Wheel type	Coating	Center bore	Pitch circle	No. of studs	Offset	Weight	Load capacity	Tyre size
TEPAA228942278	6.00 x 17.5	MZ (Ø 26) IV	NL	176	225	10	113	21,4 kg	2.750 kg	205/65 R 17.5
TEPAA229100220	6.00 x 17.5	MZ (Ø 26) IV	PB	176	225	10	113	25 kg	2.750 kg	205/75 R 17.5 215/75 R 17.5 225/75 R 17.5
TEPAA228945281	6.75 x 17.5	BMZ (Ø 21) AV	NL	161	205	6	0	25,5 kg	3.000 kg	215/75 R 17.5
TEPAA228942772	6.75 x 17.5	BMZ (Ø 26) IV	NL	176	225	10	123	26,1 kg	3.000 kg	225/75 R 17.5
TEPAA228921088	6.75 x 17.5	BMZ (Ø 26) IV	NL	176	225	10	129	25,3 kg	2.750 kg	235/75 R 17.5
TEPAA229100358	6.75 x 17.5	BMZ (Ø 26) IV	PB	176	225	10	129	26 kg	3.000 kg	245/70 R 17.5
TEPAA228896320	7.50 x 19.5	MZ (Ø 26) IV	NL	221	275	8	139	27,7 kg	2.800 kg	245/70 R 19.5 265/70 R 19.5 285/70 R 19.5
TEPAA229073811	8.25 x 22.5	BMZ (Ø 26) AV	NL	281	335	10	156	41,2 kg	3.750 kg	12 R 22.5
TEPAA229100221	8.25 x 22.5	BMZ (Ø 26) AV	PB	281	335	10	154	40 kg	3.750 kg	275/70 R 22.5 285/60 R 22.5 295/60 R 22.5 295/80 R 22.5
TEPAA228963052	9.00 x 22.5	BMZ (Ø 26) AV	NL	281	335	10	162	43,1 kg	4.000 kg	13 R 22.5
TEPAA229100214	9.00 x 22.5	BMZ (Ø 26) AV	PB	281	335	10	161	41 kg	4.000 kg	295/60 R 22.5 295/80 R 22.5 315/60 R 22.5 315/70 R 22.5 315/80 R 22.5
TEPAA228939214	11.75 x 22.5	BMZ (Ø 26) AV	NL	281	335	10	0	42,2 kg	5.000 kg 	355/50 R 22.5 385/55 R 22.5 385/65 R 22.5
TEPAA229100215	11.75 x 22.5	BMZ (Ø 26) AV	PB	281	335	10	0	42 kg	5.000 kg 	
TEPAA228955113	11.75 x 22.5	MZ (Ø 26) AV	NL	281	335	10	120	44 kg	5.000 kg 	
TEPAA229100216	11.75 x 22.5	MZ (Ø 26) AV	PB	281	335	10	120	42 kg	5.000 kg 	
TEPAA229065319	11.75 x 22.5	MZ (Ø 26) AV	NL	281	335	10	135	46 kg	5.000 kg 	
TEPAA229100217	11.75 x 22.5	MZ (Ø 26) AV	PB	281	335	10	135	42 kg	5.000 kg 	
TEPAA228973732	14.00 x 19.5	MZ (Ø 26) AV	NL	281	335	10	0	40,6 kg	5.000 kg 	425/55 R 19.5
TEPAA229100218	14.00 x 19.5	MZ (Ø 26) AV	PB	281	335	10	0	43,5 kg	5.000 kg 	435/50 R 19.5
TEPAA228939688	14.00 x 19.5	MZ (Ø 26) AV	NL	281	335	10	120	40,6 kg	4.500 kg	445/45 R 19.5
TEPAA229100219	14.00 x 19.5	MZ (Ø 26) AV	PB	281	335	10	120	43,5 kg	5.000 kg 	

AV = external valve | IV = internal valve | NL = wet paint | PB = powder coating |  5.000 kg carrying load

- High quality level according to European ETRTO standards
- TÜV certificated and monitored
- Marked with "POWERED BY GERMANY"
- TPMS valve is already fitted on delivery
- Available as complete wheel
- Also ask us about aluminium truck wheels
- Was subjected to further tough tests according to OEM requirements



Complete wheel assembly with TPMS system possible!