

AXLE OVERVIEW

FRONT AXLE



HG 2153
M+S


HG 2158
M+S


HG 2159
M+S


HG 2205
M+S


HG 2206
M+S


HG 2207S
M+S


HG 2253
M+S

REAR AXLE


HG 2205
M+S


HG 2337
M+S


HG 2338
M+S


HG 2339
M+S

BUS


HG 2201
M+S

TRAILER


HG 2144
M+S


HG 2152 ECO
M+S



HG 2154T
M+S


HG 2155
M+S


HG 2156
M+S


HG 2157
M+S


HG 2158
M+S


HG 2159
M+S


HG 2160
M+S

3PMSF-marked | **M+S** -marked | Long distance | Near distance | Near distance | 5.000 kg Carrying load

- **TÜV-approved, TÜV-monitored and TÜV-certified**
- **With „POWERED BY GERMANY" designation**
- **Development and responsibility according to European standards**
- **1A Premium carcass: regroovable and retreadable**
- **ATHOS-service network**
- **Winner cost-efectiveness of the tyre economy test**
- **Available as complete wheel**

ATHOS

First choice of truck tyres



www.athos-tyre.com

FRONT-/REAR AXLE
TECHNICAL DATA



PRODUCT-RANGE	Pattern	Load / Speed	Pattern depth mm	Weight				M+S	3PMSF
215/75 R17,5	HG2159	126/124M	13,5	27 kg	D	B	72	✓	i.p.
	HG2337	126/124M	15	28 kg	E	C	74	✓	
235/75 R17,5	HG2159	143/141L	13,5	29 kg	D	B	72	✓	i.p.
	HG2337	132/130M	15	30 kg	E	C	74	✓	
245/70 R17,5	HG2159	136/134 M	13,5	32 kg	D	B	72	✓	i.p.
245/70 R19,5	HG2158	133/131M	13.5	33 kg	D	C	72	✓	i.p.
13 R22,5	HG2205	156/150L	15	68 kg	D	C	72	✓	i.p.
13 R22,5	HG2339	156/150K	22,5	77 kg	E	B	75	✓	
295/60 R22,5	HG2206	150/147 M	15	49 kg	D	C	73	✓	i.p.
	HG2337	150/147 M	18	52 kg	D	C	75	✓	
295/80 R22,5	HG2206	152/148M	16,5	62 kg	D	B	73	✓	
	HG2337	152/148M	20,5	63 kg	E	C	74	✓	
315/60 R22,5	HG2206	152/148 M	15	52 kg	D	C	73	✓	i.p.
	HG2337	152/148 M	19	56 kg	D	C	75	✓	
315/70 R22,5	HG2206	154/150M	16	60 kg	D	B	73	✓	
	HG2207S	154/150M	16	62 kg	D	B	73	✓	
	HG2337	154/150M	20	62 kg	E	C	74	✓	
	HG2338	154/150M	20	66 kg	E	B	74	✓	
315/80 R22,5	HG2206	156/150M	16	67 kg	D	B	73	✓	
	HG2207S	156/150M	16	70 kg	D	B	73	✓	
	HG2337	156/150L	22	73 kg	E	C	74	✓	
	HG2338	156/150M	22	76 kg	E	B	74	✓	
	HG2339	156/150M	22	72 kg	E	B	75	✓	
	HG2205	156/150M	15	63 kg	D	C	72	✓	i.p.
385/55 R22,5	HG2253	164K (158L)	12,5	67 kg	C	B	71	✓	
385/65 R22,5	HG2153	164K (158L)	13	72 kg	C	B	70	✓	

TRAILER
TECHNICAL DATA

POWERED BY GERMANY

The clearly visible „Powered by Germany" label indicates that our ATHOS truck tyres are manufactured according to German standards and specifications. We pay particular attention to a careful selection of raw materials and a constant development of the tyre according to the requirements of European vehicle manufacturers.



PRODUCT-RANGE	Pattern		Load / Speed	Pattern depth mm	Weight				M+S	3PMSF
215/75 R17,5	HG2159		135/133L	13,5	27 kg	D	B	72	✓	i.p.
235/75 R17,5	HG2159		143/141L	13,5	29 kg	D	B	72	✓	i.p.
245/70 R17,5	HG2159		143/141J	13,5	32 kg	D	B	72	✓	i.p.
245/70 R19,5	HG2158		141/140J	13,5	33 kg	D	C	72	✓	i.p.
265/70 R19,5	HG2160		143/141J	13,5	38 kg	E	D	71	✓	i.p.
385/55 R22,5	HG2155	5t	164J	15	69 kg	C	B	73	✓	
385/55 R22,5	HG2144[2]	5t	164J	15	69 kg	i.p.	i.p.	i.p.	✓	i.p.
385/65 R22,5	HG2156	5t	164J	14,5	73 kg	C	B	73	✓	
385/65 R22,5	HG2144[2]	5t	164J	18	73 kg	i.p.	i.p.	i.p.	✓	i.p.
385/65 R22,5	HG2152**ECO**	5t	164J	11,5	69 kg	B	B	72	✓	i.p.
385/65 R22,5	HG2154T	5t	164J	17	76 kg	C	C	73	✓	
435/50 R19,5	HG2157	5t	164J	12,5	69 kg	B	B	73	✓	i.p.
445/45 R19,5	HG2157	5t	164J	13	70 kg	B	B	73	✓	i.p.

BUS:

275/70 R22,5	HG2201[1]	148/145J	19,2	50 kg	C	B	70	✓	

5t 5.000 kg carrying load

1) With side wall protection for buses and 5 mm depth indicator

2) Currently still in testing phase

i.p. – in preparation

SAFE ON THE ROAD
WIDER TREAD & 3PMSF CERTIFIED

From now on even safer on the road with our HG2207S and HG2338. The widened running surface optimizes the weight distribution over the road grip and improves cornering. Even winter weather conditions are no problem for our profiles - thanks to monitored endurance tests on snow and ice.

www.athos-tyre.com

